

TOPLOADER TL



MAIN APPLICATION AREAS:

- Maintenance organisations
- Repair shops
- Intermediate cleaning steps

Workplace implement



EQUIPMENT CHARACTERISTICS:

- All components in contact with fluid in stainless steel
- **Vertically** rotating cage
- Motor-driven cleaning cage
- High loading capacity (max. payload 350 kg)
- Siemens electrical equipment with Siemens Logo control
- Highly efficient and powerful Grundfos pump IE3/IE4
- Dry running protection
- Tank cover

BUPI CLEANER® TOPLOADER TL

OVERALL DIMENSIONS APPROX. (WITHOUT ADDITIONAL EQUIPMENT)	TL 80	TL 100	TL 120
Wire basket, round	1,000 mm	1,000 mm	1,200 mm
Usable height	450 mm	500 mm	700 mm
Width	1,120 mm	1,320 mm	1,520 mm
Depth	920 mm	1,120 mm	1,320 mm
Height with closed lid	1,000 mm	1,200 mm	1,400 mm
Payload	200 kg	250 kg	350 kg
Capacity tank	135 l	300 l	430 l
Spray pressure at the nozzles	3.0 bar	3.5 bar	3.5 bar
Circulation rate	4.8 m ³ /h	12 m ³ /h	12 m ³ /h
Pump motor	0.85 kW	2.2 kW	2.2 kW
Power electric heater	4.5 kW	6.0 kW	9.0 kW
Installed load	6.0 kW	8.5 kW	11.5 kW
Maximum current drain	10.0 A	14.5 A	20.5 A
Treatment temperature adjustable	0–85° C	0–85° C	0–85° C
Warm-up period tank from 15 to 70° C	approx. 1.5 hours	approx. 2 hours	approx. 2 hours



For further information, visit

www.bupicleaner.com

