



# TOPLOADER TL-K



## MAIN APPLICATION AREAS:

- Bulk material
- Maintenance organisations
- Repair shops
- Intermediate cleaning steps

Workplace implement



## EQUIPMENT CHARACTERISTICS:

- All components in contact with fluid in stainless steel
- **Horizontally** rotating, lockable basket holder
- Motor-driven cleaning cage
- Siemens electrical equipment with Siemens Logo control
- Highly efficient and powerful Grundfos pump IE3/IE4
- Dry running protection
- Tank cover

## BUPI CLEANER® TOPLOADER TL-K

OVERALL DIMENSIONS APPROX.  
(WITHOUT ADDITIONAL EQUIPMENT)

TL 80 K

Cleaning cage dimensions	471 x 321 x 200 mm
Width	1,220 mm
Depth	860 mm
Height with closed lid	1,030 mm
Payload	50 kg
Capacity tank	165 l
Spray pressure at the nozzles	3.2 bar
Circulation rate	12 m <sup>3</sup> /h
Pump motor	2.8 kW
Power electric heater	6.0 kW
Installed load	8.9 kW
Maximum current drain	10.5 A
Treatment temperature adjustable	0–85° C
Warm-up period of the tank from 15 to 70° C	approx. 1.5 hours



For further information, visit

[www.bupicleaner.com](http://www.bupicleaner.com)

